DIGITAL 6 CHANNEL ELECTROCARDIOGRAPH MONITOR - 600G



FEATURES:

- 7" TFT, touch screen, LED backlight
- Soft Touch Silicone Buttons
- Digital isolation technology and signal PRO-cessing solution, digital filter
- Patient management, name and age and ID.
- Detail analysis report.
- Multi-language options: Germany, France, Italian, Turkey, etc
- Built-in lithium rechargeable battery, wide thermal printing system
- Memory: Built-in memory or mini SD Memory card. Store more than 1000 pieces of archive
- Auto-measurement, auto-analysis, and auto-interpretation.
- *Supplied with Disposable Electrodes*

SPECIFICATIONS:

MODEL:	**ECG 600G**
Product safety Type	Class I, type CF applied part, which has defibrillation – proof applied part
Leads	Standard 12 Leads
Display	7" TFT Touch Screen, LED backlight
Input	Floating; protection against defibrillator effect.
Input impedance	≥ 50M
Patient Leak Current	<10uA
Sampling Rate	1000Hz
Frequency Response	0.05 ~ 150Hz (-3dB)
Time Constants	>3.2s
CMRR	>100dB
Dimension of Recording Paper	110mm x 20M, Paper speed 25mm/s, 50mm/s
Sensitivity choice	5,10,20mm/mV
Measurement parameters	HR, R-R interval, P-Duration, QRS Duration, Q-T interval, T-Tc, P Axis, QRS Axis, T Axis, R(V5), S (V1), R(V5) + S(V1)
Product Safety Type	Class I, CF. Defibrillation and pacing protection
Enduring Polarization voltage	± 300mv
Noise Level	<15uVp-p
Dimension	130mm (L) x 74mm (W) x 25mm (H)
Net Weight	2.3kg